



# Fast Action Compound

Part #: 15201

## Directions

1. Shake bottle well before use.
2. Always follow paint manufacturer's recommendation for fully curing new top coats.
3. Be sure painted surface is cool to the touch.
4. For major imperfections on surface, wet sanding with 1200-1500 grit sandpaper is recommended.
5. Apply a silver dollar size amount of ~~Leveling~~ *Fast Action* Compound on surface. Place an applicator pad directly on top of the Compound. Work a 2-4 square foot section using back and forth motion at approximately 1500 RPM buffer speed. Apply adequate pressure for desired leveling speed. Rinse and dry vehicle.
6. Use a cleaning brush to clean or spur pads as necessary.
7. Finish detailing and protecting with Race Glaze Polish & Sealant using an appropriate applicator pad.

**SAFETY NOTE:** A NIOSH approved respirator is always suggested when sanding or buffing.

**CAUTION:** Avoid contact with eyes. In case of contact with eyes, immediately flush with water for at least 15 minutes. If irritation persists, call a hospital emergency room or doctor. Contains petroleum distillates. Harmful or fatal if swallowed. Keep out of reach of children and pets. Please consult the Safety Data Sheet (SDS) for full details.

PART #:	15201
UPC:	028913151923
SHIPPING WEIGHT:	2.4lbs
SIZE/QTY OPTIONS:	32oz Flip Top Bottle Case of 6 Bottles

Questions? Comments? Visit [www.raceglaze.com](http://www.raceglaze.com) or call 1.888.722.3452.